

# BETTAS® BOTTOM SUCTION SUBMERSIBLE PUMP

**EHK**

www-ehk-aquatics.com



**-BP1500B-**

**-BP3000B-**

**-BP5000B-**

Model	Code	Power	Max. Flow Rate	H/Max.(M)
<b>BP-1500B</b>	P-5724	25W	1500L/H	1.7M
<b>BP-3000B</b>	P-5724C	60W	3000L/H	2.8M
<b>BP-5000B</b>	P-5724D	110W	5000L/H	5.0M

- 1. HIGH QUALITY:** ceramic rotor is more advanced than traditional stainless steel rotor. ABS material housing, durable, corrosion resistant. in salt water and fresh water.
- 2. DURABLE:** running at a whisper-quiet level, the unique rubber design on the bottom of the pond filter can be non-slip, it can hold in place.
- 3. 360° SUCTION:** fast pumping, design with low water level, pumps water as low as 1 inch quickly. An all-round design on the base can effectively remove dirt and impurities located at the bottom of the fountain pump.
- 4. DRY RUN PROTECTION:** temperature control protection has a built-in temperature control chip. When the pump is raised to 85 degrees, the chip will automatically shut off to avoid burns.



- ABS MATERIAL SHELL

- ALL-COPPER MOVEMENT

LEAKAGE-PROOF DESIGN -

MAGNETIC LEVITATION AXIS

Voltage – AC 220-240V 50Hz

**WATER PUMP 水泵**